


# Marinelite®

## Satellite SDME GSL9000

### *Speed and Distance Measuring Equipment*



EC (MED) Certified

7" HD touch screen  
Display Instrument

Fully complies with SDME (Speed and Distance Measuring Device) standard (IEC 61023)

- > Pre-type carrier phase decoding technology, more precise orientation;
- > Beidou/GPS dual-star system with faster directional speed;
- > Advanced speed and course filtering technology to make the data more stable;
- > Built-in gyro compensation system has better heading performance;
- > It has the characteristics of fast start, signal recapture, fast heading update, and high turning rate;
- > Scientific analytical algorithms to accurately decompose the lateral movement information of the bow and stern;
- > Excellent industrial product design, stylish appearance, easy installation;
- > Standard NMEA0183 output, providing high-stability, high-precision ship heading data and positioning data for Radar, ARPA, ECDIS, AIS, Chart Plotter, Autopilot, Sonar and other marine navigation equipment;
- > Maintenance free and no recurring cost as there are no mechanical parts;
- > Optional full-touch compass display, the display is equipped with multiple display modes, the data is more intuitive, and the equipment is more convenient;
- > The equipment is not affected by water temperature and salinity, and needs to prevent complex sea conditions such as high winds and heavy rain.

## Marinelite®

NANTONG SAIYANG ELECTRONICS CO.,LTD.  
South Floor 4/5, Building 3, Maipu Technology Park, Xinsheng  
Road, Chongchuan District, Nantong City, Jiangsu Province  
TEL: +86 0513-89129287/89129288  
FAX: +86 0513-81105383  
EMAIL: [Saiyang@ova.com.cn](mailto:Saiyang@ova.com.cn)  
WEB: [www.ova.com.cn](http://www.ova.com.cn)

## SARKISIAN

sea serenity

ELECTRONICS AND TELECOMMUNICATION

TEL: +30 698 3673155  
EMAIL: [info@seaserenity.net](mailto:info@seaserenity.net)  
WEB: [www.seaserenity.net](http://www.seaserenity.net)

# Satellite SDME GSL9000

## Specification

SPEED ACCURACY  
DISTANCE ACCURACY

Better than 0.2kn or 2%. Whatever is greater  
Error not exceeding 2% or 0.2nm/h of the distance traveled in each hour  
whichever value is greater.


RANGE OF SPEED  
RANGE OF DISTANCE

-99.9~99.9kn  
-0~9999.9nm


DATA INTERFACE  
COMPASS SAFE DISTANCE  
POWER SUPPLY

NMEA0183, AD-10  
55cm  
DC 24V (11V~36V)

## System Diagram



## Dimensions



**Marinelite**®

NANTONG SAIYANG ELECTRONICS CO.,LTD.  
South Floor 4/5, Building 3, Maipu Technology Park, Xinsheng  
Road, Chongchuan District, Nantong City, Jiangsu Province  
TEL: +86 0513-89129287/89129288  
FAX: +86 0513-81105383  
EMAIL: [Saiyang@ova.com.cn](mailto:Saiyang@ova.com.cn)  
WEB: [www.ova.com.cn](http://www.ova.com.cn)

**SARKISIAN**  
*sea serenity*

ELECTRONICS AND TELECOMMUNICATION

TEL: +30 698 3673155  
EMAIL: [info@seaserenity.net](mailto:info@seaserenity.net)  
WEB: [www.seaserenity.net](http://www.seaserenity.net)