

MiniPlex-3E

The MiniPlex-3E is an advanced multiplexer which combines NMEA 0183 data from multiple sources into one stream.

It also has two NMEA 0183 outputs and an Ethernet port, and received NMEA 0183 sentences can be individually be routed to each of these outputs.

The Ethernet port is bi-directional, so it can transmit NMEA 0183 data onto an Ethernet network and at the same time, it can receive NMEA 0183 data to be routed to one or both NMEA 0183 outputs. Thus, NMEA 0183 data can be distributed to multiple devices connected to the network.


Communication speeds up to 115200 baud are supported.

SeaTalk

Input 1 can be set to SeaTalk mode, so it can transmit and receive SeaTalk data. Received SeaTalk data is converted to NMEA 0183 while NMEA 0183 data from any input or Ethernet port can be selectively routed and converted to the SeaTalk port.

All NMEA 0183 inputs, outputs and Ethernet port are galvanically isolated, thus preventing any chance of ground loops.

A comprehensive set of features include routing/filtering of NMEA 0183 sentences, numerous conversions, prioritisation of data etc. make the MiniPlex-3E the ultimate solution for any interfacing requirement.



MiniPlex-3E Technical specifications

Supply voltage:	8-35 V _{DC} , protected against reversed polarity
Current consumption:	100 mA (150 mA max. with fully loaded talker ports)
Host interface:	10BASE-T/100BASE-TX Ethernet
Supported protocols:	TCP or UDP, port 10110 for NMEA communication TCP, port 10110 for firmware updates TCP and UDP, port 30718 for network configuration ARP, ICMP and DHCP for network management
Inputs:	4 x NMEA 0183/RS422, galvanically isolated In 1 can be set to SeaTalk mode
Input resistance:	> 1.4 kOhm
Input current:	0.5 mA @ 2 V 3.0 mA @ 5 V 7.1 mA @ 10 V
Outputs:	2 x NMEA 0183/RS422, galvanically isolated Out 2 can be switched to RS485/Modbus-RTU
Max output current:	20 mA @ > 2 V
Routing table size:	50 sentence types
Priority table size:	50 sentence types
Speed NMEA 0183 inputs:	4800 - 115200 baud
Speed NMEA 0183 Outputs:	4800 - 115200 baud
Indicators:	Overflow and Data
Housing:	Flame retardant ABS
Dimensions:	138 x 62 x 30 mm