

MiniPlex-3USB

The MiniPlex-3USB is an advanced multiplexer which combines NMEA 0183 data from multiple sources into one stream.

It also has two NMEA 0183 outputs and a USB port, and received NMEA 0183 sentences can be individually be routed to each of these outputs.

The USB port is bi-directional, so it can transmit NMEA 0183 data to a connected computer and at the same time, it can receive NMEA 0183 data to be routed to one or both NMEA 0183 outputs.

Communication speeds up to 115200 baud are supported.

SeaTalk

Input 1 can be set to SeaTalk mode, so it can transmit and receive SeaTalk data. Received SeaTalk data is converted to NMEA 0183 while NMEA 0183 data from any input or USB port can be selectively routed and converted to the SeaTalk port.

All NMEA 0183 inputs, outputs and USB port are galvanically isolated, thus preventing any chance of ground loops.

comprehensive set of features include routing/filtering of NMEA 0183 sentences, numerous conversions, prioritisation of data etc. make the MiniPlex-3USB the ultimate solution for any interfacing requirement.



MiniPlex-3USB Technical specifications

Supply voltage:	8-35 V _{DC} , protected against reversed polarity
Current consumption:	50 mA (100 mA max. with fully loaded talker ports)
Host interface:	USB, galvanically isolated Internal speed: 460800 baud
Inputs:	4 x NMEA 0183/RS422, galvanically isolated In 1 can be set to SeaTalk mode
Input resistance:	> 1.4 kOhm
Input current:	0.5 mA @ 2 V 3.0 mA @ 5 V 7.1 mA @ 10 V
Outputs:	2 x NMEA 0183/RS422, galvanically isolated Out 2 can be switched to RS485/Modbus-RTU
Max output current:	20 mA @ > 2 V
Routing table size:	50 sentence types
Priority table size:	50 sentence types
Speed NMEA 0183 inputs:	4800 - 115200 baud
Speed NMEA 0183 Outputs:	4800 - 115200 baud
Indicators:	Overflow and Data
Housing:	Flame retardant ABS
Dimensions:	138 x 62 x 30 mm